



# CONVENTIONAL AUTOMOTIVE

ANTIFREEZE / COOLANT

PRODUCT #230

## DESCRIPTION:

Crystal Clean Conventional Automotive, prediluted, 50/50 antifreeze/coolant is ready to add to your vehicle cooling system for automotive or other light-duty use with no further dilution necessary. With technology designed for older vehicles using conventional coolant, it contains a phosphate free, inhibitor package that provides excellent all metal protection. In automobiles, light trucks, SUV's, vans and other light duty applications, this product can provide a service life of 2-3 years or up to 50,000 miles.

Crystal Clean Conventional Automotive antifreeze/coolant contains a well-balanced inhibitor system that provides great protection for all cooling system metal components. The product provides year-round protection against freeze-ups, boil-overs and engine cooling system corrosion. This antifreeze/coolant also includes ingredients to disperse minor oil leakage, prevent fouling, control hot surface scaling and it will not damage auto finishes or rubber parts.

## BENEFITS:

- Meets the performance requirements of ASTM D3306
- Ready-to-use prediluted 50/50
- Protects all system metals.
- In light-duty vehicles it will perform for up to 3 years or 50,000 miles with complete drain, flush, and refill.
- Green in color.

## PREMIX 50/50

| Characteristic           | Company Typical | ASTM Method |
|--------------------------|-----------------|-------------|
| Specific Gravity (60°F)  | 1.075           | D1122       |
| Boiling Point (50% V/V)  | 230°F**         | D1120       |
| Freezing Point (50% V/V) | -34°F           | D1177       |
| Ash content, mass %      | 1.1             | D1119       |
| pH (50% V/V)             | 10.3            | D1287       |
| Reserve alkalinity*      | 5.0             | D1121       |
| Color                    | Green           | --          |

Suitable for use in older passenger cars and light duty trucks (generally pre-2002) which require a conventional antifreeze/coolant. Reference owners manual for proper application

- Chrysler
- Ford
- General Motors
- Other applications following owners manual

This product contains a limited warranty. Please visit <https://www.crystal-clean.com/af-warranty> for full details. Follow OEM recommendations for specified maintenance.

\*Reserve alkalinity (RA) is a value agreed between the customer and supplier. The RA listed above is the typical for the additive package being used.

\*\*Boiling point shown at atmospheric pressure. Add 40°F for 15 psi radiator cap

