



LIGHT DUTY GLOBAL

NITRITE-FREE OAT
EXTENDED LIFE ANTIFREEZE/COOLANT

PRODUCT #235

DESCRIPTION:

Crystal Clean Light Duty Global antifreeze/coolant contains a pure organic acid technology (OAT) inhibitor system that is significantly more durable than conventional additive systems for automotive, light duty use, resulting in up to 5-year/150,000 mile service life. The antifreeze is suitable for use in foreign and domestic passenger cars, vans, SUVs and light trucks requiring extended life antifreeze.

The inhibitor technology used in this extended life antifreeze/coolant contains no borate, nitrate, nitrite, phosphates, silicates, or amines. It is compatible with all major brands of OAT, hybrid and conventional coolants without precipitation problems under typical top off quantities. However, mixing different coolant types should be avoided because it will shorten the life of the "mixed" coolant.

Additionally, this antifreeze/coolant contains inhibitors that protect all cooling system metals. Together with the glycol base, these inhibitors and other additives, give year-round protection against freeze-ups, boil-overs and engine cooling system corrosion.

BENEFITS:

- Meets the performance requirements of ASTM D3306
- Compatible for use in all cars, light duty trucks, and motor cycles
- Ready-to-use prediluted 50/50
- Yellow color is neutral and will not alter the original color of the coolant.

PREMIX 50/50

Characteristic	Company Typical	ASTM Method
Specific Gravity (60°F)	1.075	D1122
Boiling Point (50% V/V)	230°F**	D1120
Freezing Point (50% V/V)	-34°F	D1177
pH (50% V/V)	8.5	D1287
Reserve alkalinity*	3 mL	D1121
Color	Yellow	--

Recommended for, but not limited to, use in the following light duty applications:

- General Motors
- Mitsubishi
- Toyota
- Kia
- Chrysler
- Nissan
- Volkswagen
- Ford Motor Co
- Hyundai
- Mercedes
- Audi
- BMW

*Reserve alkalinity (RA) is a value agreed between the customer and supplier. The RA listed above is the typical for the additive package being used.

**Boiling point shown at atmospheric pressure. Add 40°F for 15 psi radiator cap

This product contains a limited warranty. Please visit <https://www.crystal-clean.com/af-warranty> for full details. Follow OEM recommendations for specified maintenance.

