

SAFETY DATA SHEET

1. Identification

Product identifier Heavy Duty Conventional Antifreeze/Coolant

Other means of identification

Synonyms HD Fully Formulated (Part # 232)

Recommended use Coolant

Manufacturer/Importer/Supplier/Distributor information

Company name Heritage-Crystal Clean, LLC **Address** 2175 Point Boulevard Suite 375

Elgin, IL 60123-9211

Telephone **Technical Questions** 877-938-7948

Website www.crystal-clean.com E-mail cc_ehs@crystal-clean.com

Emergency phone number Chemtrec 800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

> Serious eye damage/eye irritation Category 2B

Specific target organ toxicity, repeated Category 2 (Kidney)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Harmful if swallowed. Causes eye irritation. May cause damage to organs (Kidney) through

prolonged or repeated exposure.

Precautionary statement

Prevention Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when

using this product.

Response Get medical advice/attention if you feel unwell. Rinse mouth. If eye irritation persists: Get

medical advice/attention.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Ethylene Glycol	107-21-1	>45

Composition comments Components not listed are either non-hazardous or are below reportable limits.

Issue date: 09-March-2015

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eve contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed **General information** Abdominal pain. Convulsions. Edema. Dizziness. Nausea, vomiting. Irritation of eyes and mucous membranes. Irritation of nose and throat. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim

under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage Precautions for safe handling

Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Use care in handling/storage.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Heavy Duty Conventional Antifreeze/Coolant #232 SDS US 2/7 Version #: 04 Revision date: 22-November-2017 Issue date: 09-March-2015

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components Type Value **Form** Ethylene Glycol (CAS 107-21-Ceiling 100 mg/m3 Aerosol.

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear a chemical respirator with organic

vapor cartridge and full face piece if the atmosphere cannot be maintained under the exposure

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece. Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Keep away from food and drink. Always observe good personal hygiene measures, such as considerations washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Color Green. Odor Mild

Odor threshold Not available.

Ha 9.5 - 10.8 ASTM E-70

-34 °F (-36.67 °C) ASTM D-1177 Melting point/freezing point

Initial boiling point and boiling 265 °F (129.44 °C) (50% in water using 15 lb

range radiator cap)

Flash point > 200.0 °F (> 93.3 °C) Pensky-Martens Closed Cup

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Not available. Vapor density Not available. Relative density 1.06 - 1.09

Solubility(ies)

Solubility (water) Soluble

Heavy Duty Conventional Antifreeze/Coolant #232 Issue date: 09-March-2015 Partition coefficient (n-

octanol/water)

Not available.

Auto-ignition temperature Decomposition temperature Not available. Not available.

Viscosity

Not available.

Other information

Density 8.82 lb/gal

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials. Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. Prolonged

inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes eye irritation. Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Abdominal pain. Convulsions. Edema. Dizziness. Nausea, vomiting. Irritation of nose and throat. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing,

redness, and discomfort. Skin irritation.

Information on toxicological effects

Harmful if swallowed. **Acute toxicity**

Components **Species Test Results**

Ethylene Glycol (CAS 107-21-1)

Acute Dermal

Rabbit LD50 9530 mg/kg

Oral

LD50 Rat 4700 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Causes eye irritation. irritation Serious eye damage/eye

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Version #: 04 Revision date: 22-November-2017 Issue date: 09-March-2015

Heavy Duty Conventional Antifreeze/Coolant #232

4/7

Specific target organ toxicity -

repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure.

Aspiration hazard

Not available.

Chronic effects

Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results**

Ethylene Glycol (CAS 107-21-1)

Aquatic

LC50 Fish

Fathead minnow (Pimephales promelas) 8050 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Not available.

Partition coefficient n-octanol / water (log Kow)

Ethylene Glycol (CAS 107-21-1)

-1.36

Mobility in soil

Expected to be slightly to moderately mobile in soil.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container

is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

Non Bulk packages (<10000 pounds) are not regulated as dangerous goods.

DOT BULK

BULK

UN number NA3082

UN proper shipping name Other regulated substances, liquid n.o.s. (Ethylene glycol RQ = 5000 LBS)

Transport hazard classe(es)

Class 9 9 Label(s) **Packing group**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IB3, T2, TP1 Special provisions

155 **Packaging exceptions** 203 Packaging non bulk Packaging bulk 241

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethylene Glycol (CAS 107-21-1) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity

Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt.

Ethylene Glycol 107-21-1 >45

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylene Glycol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

US. - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Ethylene glycol (CAS 107-21-1)

US. Massachusetts RTK - Substance List

Ethylene Glycol (CAS 107-21-1)

US. New Jersey Worker and Community Right-to-Know Act

Ethylene Glycol (CAS 107-21-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethylene Glycol (CAS 107-21-1)

US. Rhode Island RTK

Ethylene Glycol (CAS 107-21-1)

SDS US Issue date: 09-March-2015

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

Europe European List of Notified Chemical Substances (ELINCS)

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

New Zealand

New Zealand Inventory

Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

Issue date 09-March-2015 **Revision date** 22-November-17

Version # 04

HMIS® ratings Health: 2*

Flammability: 1 Physical hazard: 0

Disclaimer Heritage-Crystal Clean, LLC cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Heavy Duty Conventional Antifreeze/Coolant #232

Version #: 04 Revision date: 22-November-2017 Issue date: 09-March-2015 7 / 7

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).