SAFETY DATA SHEET



1. Identification

Product identifier Heavy Duty Extended Life Premium (NMOAT) Antifreeze/Coolant

Other means of identification

Product code 237 Recommended use Coolant **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Heritage-Crystal Clean, LLC Company name 2175 Point Boulevard Suite 375 **Address**

Elgin, IL 60123-9211

Technical Questions 877-938-7948 Telephone

Website www.crystal-clean.com E-mail cc ehs@crystal-clean.com

Chemtrec 800-424-9300 **Emergency phone number**

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

> Serious eye damage/eye irritation Category 2B Reproductive toxicity Category 2

Specific target organ toxicity, repeated Category 2 (Kidney)

exposure

OSHA defined hazards Not classified.

Label elements





Signal word Warning

Hazard statement Harmful if swallowed. Causes eye irritation. Suspected of damaging fertility or the unborn child.

May cause damage to organs (Kidney) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

> and understood. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face

protection.

If swallowed: Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel Response

unwell. Rinse mouth. If eye irritation persists: Get medical advice/attention. If exposed or

concerned: Get medical advice/attention.

Storage Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Heavy Duty Extended Life Premium (NMOAT) Antifreeze/Coolant 1/7 933153 Version #: 02 Revision date: 06-July-2017 Issue date: 21-April-2016

Chemical name	CAS number	%	
Ethylene Glycol	107-21-1	>45	
Diethylene glycol	111-46-6	<5	
Hexanoic Acid, 2-ethyl-potassium salt	3164-85-0	<3	

Composition comments

Components not listed are either non-hazardous or are below reportable limits. All concentrations are in percent by weight unless otherwise indicated.

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Skin contact

Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

General information

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Abdominal pain. Convulsions. Edema. Dizziness. Nausea, vomiting. Irritation of eyes and mucous membranes. Irritation of nose and throat. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions
Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Do not taste or

swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial

hygiene practices. Use care in handling/storage.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10

of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

110	ACCIL	Threshold	Limit	Value
US.	AUGIN	Threshold		values

Components	Туре	Value	Form
Ethylene Glycol (CAS 107-21-1)	Ceiling	100 mg/m3	Aerosol.
US. Workplace Environmental E	xposure Level (WEEL) Guides		
Components	Туре	Value	
Diethylene glycol (CAS	TWA	10 mg/m3	

Biological limit values

111-46-6)

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear a chemical respirator with organic vapor

cartridge and full face piece if the atmosphere cannot be maintained under the exposure limits.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Red.
Odor Mild.

Odor threshold Not available.

pH 8 - 9

Melting point/freezing point Not available.

Initial boiling point and boiling

range

265 °F (129.44 °C) 50% water using 15 lb radiator cap

Flash point > 200.0 °F (> 93.3 °C) Pensky-Martens Closed Cup

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

> 1

Vapor pressure Not available.

Vapor density

Relative density 1.06 - 1.09 at 68°F

Solubility(ies)

Solubility (water) Completely Soluble

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Bulk density 8.9 lbs/gal

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. Prolonged

inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes eye irritation. **Ingestion** Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Abdominal pain. Convulsions. Edema. Dizziness. Nausea, vomiting. Irritation of nose and throat. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing,

redness, and discomfort. Skin irritation.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Components Species Test Results

Diethylene glycol (CAS 111-46-6)

<u>Acute</u> Dermal

LD50 Rabbit 11890 mg/kg

Ethylene Glycol (CAS 107-21-1)

Acute Dermal

LD50 Rabbit 9530 mg/kg

Oral

LD50 Rat 4700 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Heavy Duty Extended Life Premium (NMOAT) Antifreeze/Coolant
933153 Version #: 02 Revision date: 06-July-2017 Issue date: 21-April-2016

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Ethylene Glycol (CAS 107-21-1)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 8050 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethylene Glycol (CAS 107-21-1) -1.36

Mobility in soil Expected to be slightly to moderately mobile in soil.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

Non Bulk packages (<10000 pounds) are not regulated as dangerous goods.

DOT BULK

BULK

UN number NA3082

UN proper shipping name Other regulated substances, liquid, n.o.s. (Ethylene glycol RQ = 5000 LBS)

Transport hazard class(es)

Class 9

Label(s) 9
Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3, T2, TP1

Packaging exceptions 155
Packaging non bulk 203
Packaging bulk 241

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethylene Glycol (CAS 107-21-1) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Ethylene Glycol	107-21-1	>45

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylene Glycol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

WARNING: This product contains a chemical known to the State of California to cause birth

defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Ethylene Glycol (CAS 107-21-1)

US. Massachusetts RTK - Substance List

Ethylene Glycol (CAS 107-21-1)

US. New Jersey Worker and Community Right-to-Know Act

Ethylene Glycol (CAS 107-21-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Diethylene glycol (CAS 111-46-6) Ethylene Glycol (CAS 107-21-1)

Heavy Duty Extended Life Premium (NMOAT) Antifreeze/Coolant

SDS US

US. Rhode Island RTK

Diethylene glycol (CAS 111-46-6) Ethylene Glycol (CAS 107-21-1)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date21-April-2016Revision date06-July-2017

Version # 02

HMIS® ratings Health: 2*

Flammability: 1 Physical hazard: 0

NFPA ratings



Disclaimer

Heritage-Crystal Clean, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Heavy Duty Extended Life Premium (NMOAT) Antifreeze/Coolant SDS US 933153 Version #: 02 Revision date: 06-July-2017 Issue date: 21-April-2016 7 / 7

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).